

# 30/00140 fluidising additive

ADDITIVE FOR IMPROVING FLUIDISABILITY

## Typical application

- insufficient fluidisation
- powder puffs
- to improve processing with DDF pumps

## Features

- suitable for all TIGER Drylac® series
- additive in powder form
- good storage stability
- improves the flowability
- counteracts clumping when DDF pumps are used

**Packaged** in original 2 kg cartons and in 150g and 300g minipacks

**Shelf life** 12 months from delivery, in a dry place at below 25°C, protected from direct heat

## How to use

TIGER 30/00140 fluidising additive is added, dry, to TIGER Drylac® in an admixture ratio of between 0.05% and 0.1%, as required, and then thoroughly mixed. The resulting mixture must be completely homogeneous; we recommend screening it as well. Additional mixing generally takes place in the hopper.

Admixture ratio in terms of weights and volumes

Quantity of coating powder	Admixture of 0.05% fluidising additive	
	Weight	Volume
20 kg	10 g	200 ml
25 kg	12,5 g	250 ml

Admixture ratios higher than 0.1 % can cause flow-difficulties and charge-problems.

Our verbal and written recommendations for the use of our products are based upon experience and in accordance with present technological standards. These are given in order to support the buyer or user. They are non-committal and do not create any additional commitments to the purchase agreement. They do not release the buyer from verifying the suitability of our products for the intended application. We warrant that our products are free of flaws and defects to the extent as stipulated in our Terms of Delivery and Payment.

As a part of our product information program each of our Product Data Sheets are periodically updated, so that the latest version shall prevail. Therefore, please visit the download area of [www.tiger-coatings.com](http://www.tiger-coatings.com) to make sure you have the most current version of this Product Data Sheet. The information in our Product Data Sheets is subject to change without notification.

This Product Data Sheet substitutes any and all previous Product Data Sheets and notes for customers published on this subject matter and is only intended to give a general product overview. Please request specific information for products outside of our standard product list (latest version).

The Technical Information Sheets and the Terms of Delivery and Payment each in their latest version, available as a download at [www.tiger-coatings.com](http://www.tiger-coatings.com), form an integral part of this Product Data Sheet.

certified according to  
EN ISO 9001 / 14001



**TIGER Coatings GmbH & Co. KG**

Negrellistrasse 36 | 4600 Wels | Austria

T +43 / (0)7242 / 400-0

F +43 / (0)7242 / 650 08

E [powdercoatings@tiger-coatings.com](mailto:powdercoatings@tiger-coatings.com)

W [www.tiger-coatings.com](http://www.tiger-coatings.com)

30/00140