

SERIES 44 - gloss killer (44/00006)

POLYURETHANE POWDER MATTING AGENT FOR POST ADDITION TO SMOOTH FLOW POWDER COATING

Typical applications

- interior applications: suitable for all TIGER Drylac® products
- exterior applications: suitable only in conjunction with TIGER Drylac® Series 39, 49, 59, 139 and 149.

NOT SUITABLE for architectural applications

Product details

Standard packaging in original 44 lb (20 kg) box and 5 lb (2.5 kg) minipack

Storage stability 6 months at no more than 77 °F (25 °C) avoid direct and extended exposure to heat

Features

- achieve continuous matting from 30-60 gloss*
- suitable for all interior TIGER Drylac® products

Finish

finish	gloss	note
semi-gloss	55-65*	add 10-20% to the powder coating
matte	16-25*	add 20-30% to the powder coating

Concentration

The gloss killer agent should be equivalent to 10-30% of the total weight of the powder coating. Any mix in excess of 30% may result in reduced hiding power and color change.

Please note

Verification of the optimum mixing ratios and the suitability of the processes and applications should be carried by the buyer/user prior to further processing.

Mixing

The gloss killer should be dry blended to the powder coating. While larger volumes can be mixed using drums or roll mixers, smaller volumes can be mixed manually.

This is a polyurethane-based additive; adhering to the appropriate cure schedule is imperative (for further information please refer to the most recent relevant Product Data Sheet).

Disclaimer

TIGER's verbal and written recommendations for the use of its products are based upon experience and in accordance with current technological standards. These are provided in order to support the buyer or user. They are non-committal and do not create any additional commitments to the purchase agreement. They do not release the buyer from verifying the suitability of TIGER products for the intended application. TIGER warrants that its products are free of flaws and defects to the extent stipulated in the Terms of Delivery and Payment.

As part of TIGER product information program, each Product Data Sheet is updated periodically. The latest version shall prevail. It is recommended to always check for the latest editions on TIGER's website download area www.tiger-coatings.com to make sure you have the most current version of this Product Data Sheet. The information on TIGER's Product Data Sheets are subject to change without notification.

This Product Data Sheet supersedes and replaces all previous Product Data Sheet versions and notes to customers published in relation to this product and is only intended to provide a general overview on the product.

Latest versions of Technical Information Sheets and Terms of Delivery and Payment are downloadable from www.tiger-coatings.com and form an integral part of this Product Data Sheet.