



SERIES 09 - ELECTROSTATIC DISSIPATIVE

Epoxy/Polyester hybrid powder coating for interior applications with electrostatic dissipative properties.

Typical Applications

- Computer hoods.
- Electronic cabinets.

Standard Packaging 44 & 55 lb (20 & 25 kg) boxes.
5 lb (2.5 kg) minipack.

Specific Gravity (ASTM D792) approximately 1.6 g/cm³
depending on pigmentation.

Theoretical Coverage at 1.5 specific gravity and
2.5 mils (60 µm) film thickness:
51.5 ft²/lb (11.1 m²/kg).

Refer also to the latest edition
of "Theoretic Powder Coating
Coverage Chart".
Version 00-1001 (imperial).
Version 00-1000 (metric).

Storage Stability 6 months at no more than
77 °F (25 °C).

Features

- Electrostatic dissipative.
- Resistivity between 10⁷-10⁹ Ω.

Finish and Color

- Black, smooth matte 15-25* TIGER Drylac® 09/81760

* Gloss level according to ASTM 523 at 60° angle.

Custom colors can be made available in black to dark grey colors.

For further information on this product, please refer to the TIGER Drylac® Series 09 Product Data Sheet for Interior Applications.

As part of TIGER Drylac® product information program, Product Data Sheets are updated periodically. It is recommended to always check for the latest editions on TIGER's website. TIGER's verbal and written recommendations for the use of its products are based upon experience and in accordance with current technological standards. These are given in order to support the buyer or user. They are non-committal and do not create any additional commitments to the purchase agreement. They do not release the buyer from verifying the suitability of TIGER products for the intended application. This Product Data Sheet supersedes all previous Product Data Sheet versions and notes published in relation to this product.

Certified according to
ISO 9001 | 14001

TIGER Drylac U.S.A., Inc.
3855 Swenson Avenue
St Charles, IL 60174, USA
T 800 243 8148
F 877 926 8148
E office.us@tiger-coatings.us
W www.tiger-coatings.us