

SERIES 09 - electrostatic dissipative

EPOXY/POLYESTER HYBRID POWDER COATING FOR INTERIOR APPLICATIONS WITH ELECTROSTATIC DISSIPATIVE PROPERTIES

Typical applications

- computer hoods
- electronic cabinets

Product details

| | |
|-------------------------------------|--|
| Standard packaging | in original 22, 44 & 55* lb (10, 20 & 25* kg) boxes and 5 lb (2.5 kg) minipack |
| Specific gravity (ASTM D792) | approximately 1.6 g/cm ³ depending on pigmentation |
| Theoretical coverage | at 2.5 mils (60 µm) film thickness: 51.5 ft²/lb (11.1 m²/kg) . Refer also to "Theoretic Powder Coating Coverage Chart" version 00-1001 (imperial) version 00-1000 (metric) |
| Storage stability | 12 months at no more than 77 °F (25 °C) avoid direct and extended exposure to heat *Available while quantities last |

Features

- electrostatic dissipative
- resistivity between 10⁷-10⁹ Ω

Finish

| finish | gloss |
|---------------------|--------|
| smooth <i>matte</i> | 15-25* |

* Gloss level according to ASTM 523 at 60° angle (doesn't apply to metallic effect powder coatings). The measured gloss level of effect powder coatings can diverge from the details given in this Product Data Sheet. The creation of tolerance samples is recommended.

Available as stock product in the following colors:

| product description | product ID |
|---------------------|------------|
| Black Conductive | 09/81760 |

Custom-colors can be made to order in black to dark grey colors (minimum order quantity applies).

For further information on this product, please refer to the TIGER Drylac® Series 09 Product Data Sheet for interior applications.

Certified according to
ISO 9001 | 14001

Disclaimer

TIGER's verbal and written recommendations for the use of its products are based upon experience and in accordance with current technological standards. These are provided in order to support the buyer or user. They are non-committal and do not create any additional commitments to the purchase agreement. They do not release the buyer from verifying the suitability of TIGER products for the intended application. TIGER warrants that its products are free of flaws and defects to the extent stipulated in the Terms of Delivery and Payment.

As part of TIGER product information program, each Product Data Sheet is updated periodically. The latest version shall prevail. It is recommended to always check for the latest editions on TIGER's website download area www.tiger-coatings.com to make sure you have the most current version of this Product Data Sheet. The information on TIGER's Product Data Sheets are subject to change without notification.

This Product Data Sheet supersedes and replaces all previous Product Data Sheet versions and notes to customers published in relation to this product and is only intended to provide a general overview on the product.

Latest versions of Technical Information Sheets and Terms of Delivery and Payment are downloadable from www.tiger-coatings.com and form an integral part of this Product Data Sheet.

TIGER Drylac U.S.A., Inc.
3945 Swenson Avenue
St Charles, IL 60174, USA
T 800 243 8148
F 877 926 8148
E office.us@tiger-coatings.com
W www.tiger-coatings.com